


PV- MANUAL AIR VENT - PRESSURE / TEMPERATURE



Combination Manual Air Vent and Pressure/Temperature Test Port with brass body, dual durometer EPDM core, blowout-proof stem, side discharge vent with 1/8" (4mm) hose barb, threaded brass cap with O-ring seal and neoprene retainer strap. Accepts standard 1/8" (4mm) gauge adapter or thermometer stem. Rated to 250 PSI (1725 kPa) and 250°F (120°C).

MODEL	NPT CONN	A		B		C		WRENCH SIZE	WEIGHT	
		in	mm	in	mm	in	mm		lbs	kg
PV-025	0.25"	1.50	40	0.84	21	0.32	9	3/4"	0.154	0.07
PV-050	0.50"	1.50	40	0.98	25	0.32	9	3/4"	0.225	0.10




PX- EXTENDED MANUAL AIR VENT - PRESSURE / TEMPERATURE PORT



Extended Combination Manual Air Vent and Pressure/Temperature Test Port with brass body, dual durometer EPDM core, blowout-proof stem, side discharge vent with 1/8" (4mm) hose barb, threaded brass cap with O-ring seal and neoprene retainer strap. Accepts standard 1/8" (4mm) gauge adapter or thermometer stem. Rated to 250 PSI (1725 kPa) and 250°F (120°C).

MODEL	NPT CONN	A		B		C		WRENCH SIZE	WEIGHT	
		in	mm	in	mm	in	mm		lbs	kg
PX-025	0.25"	3.60	91	0.87	22	0.31	8	3/4"	0.28	0.12




PT-PRESSURE / TEMPERATURE PORT



Pressure/Temperature Test Port with brass body, dual durometer EPDM core, brass cap with O-ring seal and neoprene retainer strap. Accepts standard 1/8" (4mm) gauge adapter or thermometer stem. Rated to 500 PSI (3450 kPa) and 275°F (135°C).

MODEL	NPT CONN	A		B		WRENCH SIZE	WEIGHT	
		in	mm	in	mm		lbs	kg
PT-025	0.25"	1.36	34	0.65	16	9/16"	0.06	0.03
PT-050	0.50"	1.36	34	1.01	25	7/8"	0.18	0.08




PL-LOW-LEAD PRESSURE / TEMPERATURE PORT



Pressure/Temperature Test Port with Low-Lead body, dual durometer EPDM core, brass cap with O-ring seal and neoprene retainer strap. Accepts standard 1/8" (4mm) gauge adapter or thermometer stem. Rated to 500 PSI (3450 kPa) and 275°F (135°C).

MODEL	NPT CONN	A		B		WRENCH SIZE	WEIGHT	
		in	mm	in	mm		lbs	kg
PL-025	0.25"	1.36	34	0.65	16	9/16"	0.06	0.03




SX & DX - PRESSURE /TEMPERATURE PORT EXTENDER



SX Single and DX Dual Extenders for PT models, used on insulated piping systems or where extended length is desired. Extenders are installed above the PT core with an O-ring seal and can be installed in the field without removing the PT from the piping system. Brass body with EPDM O-ring seal. Rated to 500 PSI (3450 kPa) and 250°F (120°C).

MODEL	A		B		WEIGHT	
	in	mm	in	mm	lbs	kg
SX /One	1.59	41	0.54	14	0.08	0.04
DX /Two	1.59	41	0.54	14	0.08	0.04




PT/SX - PRESSURE /TEMPERATURE PORT WITH EXTENDER



Pressure/ Temperature Test Port installed on SX Single Extender, use for insulated piping systems or where extended length is desired. SX Extender is installed above the PT core with brass cap with O-ring seal and neoprene retainer strap on top.

MODEL	NPT CONN	A		B		WRENCH SIZE	WEIGHT	
		in	mm	in	mm		lbs	kg
PT/SX-025	0.25"	2.89	73.4	0.65	16	9/16"	0.15	0.07




AE-EXTENSION



Brass body Extension, 0.25" MNPT x 0.25" FNPT, use for insulated piping systems or where extended length is desired with Accessories with 0.25" MNPT connections.

MODEL	NPT CONN	A		B		WRENCH SIZE	WEIGHT	
		in	mm	in	mm		lbs	kg
AE-025	0.25"	2.09	53.2	0.56	14	9/16"	0.08	0.04




MV - MANUAL AIR VENT



Manual Air Vent with brass body, knurled operator with screwdriver slot, blowout-proof stem, and side discharge vent. Rated to 400 PSI (2760 kPa) and 250°F (120°C).

MODEL	NPT CONN	A		B		WRENCH SIZE	WEIGHT	
		in	mm	in	mm		lbs	kg
MV-025	0.25"	1.66	42	0.55	14	9/16"	0.08	0.04




EV - EXTENDED MANUAL AIR VENT



Extended Manual Air Vent with brass body, knurled operator with screwdriver slot, blowout-proof stem, and side discharge vent.
Rated to 400 PSI (2760 kPa) and 250°F (120°C).

MODEL	NPT CONN	A		B		WRENCH SIZE	WEIGHT	
		in	mm	in	mm		lbs	kg
EV-025	0.25"	2.76	70	0.55	14	9/16"	0.14	0.06




AV - AUTOMATIC AIR VENT / CHECK-VALUE



Automatic air vent with brass body, plastic float, brass seat, and EPDM seal.
Rated to 150 PSI (1035 kPa) and 240°F (115°C).

MODEL	NPT CONN		A	B	C	D	E	WRENCH SIZE	WEIGHT	
									lbs	kg
AV-025	0.25"	in	.25"	3.62"	1.56"	.50"	2.62"	7/8"	.31	0.14
		mm	6.35	92	40	13	66	22		




DV - HOSE END DRAIN VALVE



Drain Valve with forged brass body, chrome plated ball, Teflon seats, double EPDM O-ring stem seals, aluminum handle, 3/4" hose connection with cap and plastic retainer strap.
Rated to 600 PSI (4140 kPa) WOG and 250°F (120°C).

MODEL	NPT CONN	A		B		C		WEIGHT	
		in	mm	in	mm	in	mm	lbs	kg
DV-025	0.25"	1.72	44	2.04	52	1.37	35	0.30	0.13
DV-050	0.50"	2.45	62	2.77	70	1.46	37	1.46	0.65




FLUSHING ADAPTOR



Brass body Flushing Adaptor, available in 0.50", 0.75" and 1.00" sizes, connection ends feature NPSM threads and internal cone seats.
Use to connect hose ends to bypass and flush coil systems.

PART NUMBER	NPT CONN	A		B		WRENCH SIZE	WEIGHT	
		in	mm	in	mm		lbs	kg
200555	0.50"	1.10	28	0.875	22	7/8"	0.11	0.05
200109	0.75"	1.14	29	1.062	27	1"	0.14	0.06
200556	1.00"	1.47	37	1.375	35	1 1/2"	0.23	0.10



MS- MEMORY STOP



Memory Stop, Zinc Plated with position indicator and position lock screw. For use with valve handles.




EH- EXTENDED HANDLE

Valve Handle Extensions, forged brass stem and collar, for extending existing handles 2". Use for insulated piping systems or where extended length handles are desired.



EH - Extended Handle		
Fits Body Size / Model - Series		
EH - 1	EH - 2	
All 1e	All 3e	
All 2e	AB3-100	SV3-100
	AB3-125	SV3-125
	AB3-150	SV3-150
	BB3-125	MB3-125
		MB3-150



SH- SHORT LEVER HANDLE



Short Lever Valve Handle, zinc plated steel. SH is replacement for longer standard handle for limited space installation.

HT- HANGING TAG



Hanging Tag plastic, use for valve identification.