PTK 1-25 & PTK 2-25

**Pressure Temperature Test Kit** 



# **KIT CONTENTS:**

#### Gauge 2.50"

Phosphour Bronze Bourdon Tube, Black Steel Case, Chrome Bezel, Brass Socket, White Face, Black Numerals, Accuracy +/-2% Mid-Scale, Suitable for Air, Water, Oil & Gas

# Gauge Adapter

2-3/4" x 0.063" Stainless Steel Probe Type with Probe Guards

# **Available Gauge Ranges**

0-100 PSI, 0-160 PSI, 0-200 PSI, 0-300 PSI

#### **Thermometers**

Two included, Bimetal,  $5" \times 0.142"$  Stem, 1" Dial, Accuracy +/-1%, High & Low Ranges 0-220 °F & 25-125 °F, Protective Sleeve with Clip

## Carrying Case

Aluminum with Handle & Protective Foam Inserts

# PTK 1-25

(1) 2-1/2" Gauge, (1) Adaptor,

(2) Thermometers, (Select One Gauge)

#### PTK 2-25

(2) 2-1/2" Gauges, (2) Adapters,

(2) Thermometers, (Select Two Gauges)



# PTK 1-25 & PTK 2-25 Pressure Temperature Port Test Kit OPERATING INSTRUCTIONS

## **WARNING:**

All operations should be done slowly and carefully. Take all necessary safety precautions, (i.e. safety glasses, gloves, etc.) while using this kit.

# **Pressure Measurement:**

- · Slowly insert and secure Gauge Adapters into test plug
- Read and Record Pressure Measurement

# **Temperature Measurement:**

- · Slowly insert Thermometer into test plug
- Read and Record Temperature Measurement

# Storage:

- Ensure components are dry and free from water
- Return meter to case and store in temperatures above 50° F